

<b>Part number</b>	<b>RB-P2505</b>
<b>Product name</b>	<b>5 Port Full 2.5G PoE Switch</b>
Ports	5*10M/100M/1000M/2.5G RJ45 PoE port (Data/Power)
PoEStandard	1 port supports IEEE802.3at/poe++/BT (MAX_90W) 2-4 port supports IEEE802.3at/at (MAX_30W)
PoE input	Port1: 1/2(+), 3/6(-); 4/5(+), 7/8(-) Port2-4:1/2(+), 3/6(-);
Network protocol	IEEE 802.3/U、IEEE 802.3ab、IEEE 802.3bz、IEEE 802.3x
Data rate	10M/100M/1000M/2.5G Auto
CPU	MIPS-34Kc Up to 800MHz CPU
Package cache	12Mbit SRAM
Jumbo frame	up to 12KB
Bandwidth	80Gbps
Package transfer rate	28.8Mpps
MAC address	16K
Transport distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 2500/1000BASE-TX : Cat6 or later UTP(150 meter)
Led lights	PWR:LED Port:10M//100MLED(Right Green); 1G LED(Left Green); 2.5G LED(Left Orange) PoE: PoE on led
Working Temp.	-10~+55°C; 5%~90% RH Non coagulation
Storage Temp.	-40~+75°C; 5%~95% RH Non coagulation
Power	Adaptor; MAX 650W (AC100-240V 50/60HZ MAX 0.9A)
Product/Package size	160mm*112mm*31mm 193mm*131mm*91mm
Net weight/Gross weight (kg)	0.58kg/1.09kg
Install ways	Desktop (optional wall+machine hanger parts)
Lightning strike/enclosure rating	3KV 8/20us; IP30
Certification	CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	